

EMS CATALOG NO: 12668
EMS PRODUCT: Tempfix Adhesive
DATE: 11/01/2008
PAGE NUMBER: One of 2

MATERIAL SAFETY DATA SHEET

The information contained herein is based on data considered accurate. However, no warranty is expressed or implied regarding the accuracy of these data or the results to be obtained from the use thereof.

Electron Microscopy Sciences assumes no responsibility for personal injury or property damage to vendees, users or third parties caused by the material. Such vendees or users assume all risks associated with the use of the material.

ELECTRON MICROSCOPY SCIENCES

1560 INDUSTRY ROAD

P.O. BOX 550

HATFIELD PA 19440

(215) 412-8400

24 HOUR EMERGENCY PHONE NUMBER

CHEMTREC: (800) 424-9300

FOR PRODUCT AND SALES INFORMATION

CONTACT ELECTRON MICROSCOPY SCIENCES OFFICE ABOVE.

PRODUCT IDENTIFICATION

PRODUCT NAME:	Tempfix Adhesive
CHEMICAL CHARACTERISTIC:	Melting adhesive substance on EVY basis.
FORM:	Granulated
COLOR:	Yellow
SMELL:	Product specific

PHYSICAL/CHEMICAL AND SAFETY INDICATIONS

CHANGING OF THE CONDITION:	Fluid from approximately 100°C.
DENSITY(20°C):	Couch density approximately 0.95 g/cm ₃
VAPOR PRESSURE:	None.
VISCOSITY(180°C):	Approximately 3.500
SOLUBILITY IN WATER:	Insoluble
PH:	None
INFLAMMABLE POINT:	From approximately 220°C flammable vapor
IGNITION TEMPERATURE:	Unknown
POINT OF EXPLOSION:	None
THERMAL DECOMPOSITION:	A flammable vapor is emitted at temperatures higher than 27°C.
HAZARDOUS REACTIONS:	Does not apply when used according to instructions.

HANDLING AND STORAGE DATA

EYE PROTECTION:	Use goggles
SKIN PROTECTION:	Wear Gloves
INDUSTRIAL HYGIENE:	Treat as for laboratory chemicals.
DISPOSAL:	Dispose of according to local regulations.

MEASURES IN CASE OF ACCIDENTS AND FIRES

EXTINGUISHING MEDIA:	Water mist, foam, CO ₂ , dry extinguishers.
FIRST AID:	Treat lesions produced by contact with melted product as burns.

INFORMATION ON TOXICITY

This product is not specifiable in terms of orders relating to dangerous substances.

If working temperature is exceeded over a considerable time toxic products may form. Vapor should be removed by ventilation.