

EMS CATALOG NO: 14650
EMS PRODUCT: Styrene (monomer)
DATE: 9/24/2010

MATERIAL SAFETY DATA SHEET

The information contained herein is based on data considered accurate. However, no warranty is expressed or implied regarding the accuracy of these data or the results to be obtained from the use thereof.

Electron Microscopy Sciences assumes no responsibility for personal injury or property damage to vendees, users or third parties caused by the material. Such vendees or users assume all risks associated with the use of the material.

ELECTRON MICROSCOPY SCIENCES

1560 INDUSTRY ROAD
P.O. BOX 550
HATFIELD PA 19440
(215) 412-8400

24 HOUR EMERGENCY PHONE NUMBER
CHEMTREC: (800) 424-9300

FOR PRODUCT AND SALES INFORMATION
CONTACT ELECTRON MICROSCOPY SCIENCES OFFICE ABOVE.

PRODUCT IDENTIFICATION

COMMON NAME: Styrene (monomer)
CATALOG CODES: 14650
CAS#: 100-42-5
RTECS: WL3675000
TSCA: .TSCA 8(b) Inventory: Styrene (monomer)
CI#: .Not Available
SYNONYM: Vinylbenzene
CHEMICAL FORMULA: C₈H₈

COMPOSITION AND INFORMATION ON INGREDIENTS

NAME: Styrene (monomer)

CAS#: 100-42-5

% BY WEIGHT: 100

TOXICOLOGICAL DATA ON INGREDIENTS: Styrene (monomer): ORAL (LD50): Acute: 2,650 mg/kg [Rat]. 316 mg/kg [Mouse]. VAPOR (LC50): Acute: 12000 ppm 4 hour(s) [Rat]. 9500 ppm 4 hour(s) [Mouse]..

HAZARDS IDENTIFICATION

POTENTIAL ACUTE HEALTH EFFECTS: Very hazardous in case of eye contact (irritant). Hazardous in case of skin contact (irritant, permeator), of ingestion, of inhalation. Inflammation of the eye is characterized by redness, watering, and itching.

POTENTIAL CHRONIC HEALTH EFFECTS: CARCINOGENIC EFFECTS: Classified + (PROVEN) by OSHA. Classified 2B (Possible for human.) by IARC. A4 (Not classifiable for human or animal.) by ACGIH, **MUTAGENIC EFFECTS:** Not available.

TERATOGENIC EFFECTS: Not available. **DEVELOPMENTAL TOXICITY:** Not available. The substance is toxic to the nervous system, upper respiratory tract. Repeated or prolonged exposure to the substance can produce target organs damage.

FIRST AID MEASURES

EYE CONTACT: Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Cold water may be used. Do not use an eye ointment. Seek medical attention.

SKIN CONTACT: After contact with skin, wash immediately with plenty of water. Gently and thoroughly wash the contaminated skin with running water and non-abrasive soap. Be particularly careful to clean folds, crevices, creases and groin. Cover the irritated skin with an emollient. If irritation persists, seek medical attention. Wash contaminated clothing before reusing.

SERIOUS SKIN CONTACT: Wash with a disinfectant soap and cover the contaminated skin with an anti-bacterial cream. Seek immediate medical attention.

INHALATION: Allow the victim to rest in a well ventilated area. Seek immediate medical attention.

SERIOUS INHALATION: Not available.

INGESTION: Do not induce vomiting. Examine the lips and mouth to ascertain whether the tissues are damaged, a possible indication that the toxic material was ingested; the absence of such signs, however, is not conclusive. Loosen tight clothing such as a collar, tie, belt, or waistband. If the victim is not breathing, perform mouth-to-mouth resuscitation. Seek immediate medical attention.

SERIOUS INGESTION: Not available.

FIRE AND EXPLOSION DATA

FLAMMABILITY OF THE PRODUCT: Flammable

AUTO-IGNITION TEMPERATURE: 490°C (914°F)

FLASH POINTS: CLOSED CUP: 31.1°C (88°F). (Cleveland) OPEN CUP: 36.7°C (98.1°F) (TAG).

FLAMMABLE LIMITS: LOWER: 1.1% UPPER: 6.1%

PRODUCTS OF COMBUSTION: These products are carbon oxides (CO, CO₂).

FIRE HAZARDS IN PRESENCE OF VARIOUS SUBSTANCES: Flammable in presence of open flames and sparks. Slightly flammable to flammable in presence of heat.

EXPLOSION HAZARDS IN PRESENCE OF VARIOUS SUBSTANCES: Risks of explosion of the product in presence of mechanical impact: Not available. Risks of explosion of the product in presence of static discharge: Not available.

FIRE FIGHTING MEDIA AND INSTRUCTIONS: Flammable liquid, soluble or dispersed in water.

SMALL FIRE: Use DRY chemical powder.

LARGE FIRE: Use alcohol foam, water spray or fog. Cool containing vessels with water jet in order to prevent pressure build-up, auto-ignition or explosion.

SPECIAL REMARKS ON FIRE HAZARDS: Not available.

SPECIAL REMARKS ON EXPLOSION HAZARDS: Not available.

ACCIDENTAL RELEASE MEASURES

Small Spill: Absorb with an inert material and put the spilled material in an appropriate waste disposal.

Large Spill: Flammable liquid. Keep away from heat. Keep away from sources of ignition. Stop leak if without risk. Absorb with DRY earth, sand or other non-combustible material. Do not touch spilled material. Prevent entry into sewers, basements or confined areas; dike if needed. Eliminate all ignition sources. Be careful that the product is not present at a concentration level above TLV. Check TLV on the MSDS and with local authorities.

HANDLING AND STORAGE

PRECAUTIONS: Keep locked up. Keep away from heat. Keep away from sources of ignition. Ground all equipment containing material. Do not ingest. Do not breathe gas/fumes/vapor/spray. In case of insufficient ventilation, wear suitable respiratory equipment if ingested, seek medical advice immediately and show the container or the label. Avoid contact with skin and eyes.

STORAGE: Flammable materials should be stored in a separate safety storage cabinet or room. Keep away from heat. Keep away from sources of ignition. Keep container tightly closed. Keep in a cool, well-ventilated place. Ground all equipment containing material. A refrigerated room would be preferable for materials with a flash point lower than 37.8°C (100°F).

EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls: Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective threshold limit value. Ensure that eye-wash stations and safety showers are proximal to the work-station location.

Personal Protection: Splash goggles. Lab coat. Vapor respirator. Be sure to use an approved/certified respirator or equivalent. Gloves.

Personal Protection in Case of a Large Spill: Splash goggles. Full suit. Vapor respirator. Boots. Gloves. A self-contained breathing apparatus should be used to avoid inhalation of the product. Suggested protective clothing might not be sufficient; consult a specialist BEFORE handling this product.

Exposure Limits: TWA: 50 STEL: 100 (ppm) TWA: 213 STEL: 426 (mg/m³) Consult local

authorities for acceptable exposure limits.

PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE AND APPEARANCE: Liquid (Clear viscous liquid).

ODOR: Sweetish. Aromatic.

TASTE: Not available.

COLOR: Colorless.

MOLECULAR WEIGHT: 104.14 g/mole

pH (1% SOLN/WATER): Not available.

BOILING POINT: 145.2°C (293.4°F)

MELTING POINT: -30.6°C (-23.1°F)

CRITICAL TEMPERATURE: Not available.

SPECIFIC GRAVITY: 0.906 (Water = 1)

VAPOR PRESSURE: 4.5 mm of Hg (@20°C)

VAPOR DENSITY: 3.59 (Air = 1)

VOLATILITY: Not available.

ODOR THRESHOLD: 0.1 ppm

WATER/OIL DIST. COEFF.: The product is equally soluble in oil and water; log (oil/water) = 0

IONICITY (IN WATER): Not available.

DISPERSION PROPERTIES: Not available.

SOLUBILITY: Very slightly soluble in cold water.

STABILITY AND REACTIVITY DATA

STABILITY: The product is stable.

INSTABILITY TEMPERATURE: Not available.

CONDITIONS OF INSTABILITY: Not available.

INCOMPATIBILITY WITH VARIOUS SUBSTANCES: Not available.

CORROSIVITY: Non-corrosive in presence of glass.

SPECIAL REMARKS ON REACTIVITY: Not available.

SPECIAL REMARKS ON CORROSIVITY: Not available.

POLYMERIZATION: No.

TOXICOLOGICAL INFORMATION

ROUTES OF ENTRY: Dermal contact. Eye contact. Inhalation. Ingestion.

TOXICITY TO ANIMALS: WARNING: THE LC50 VALUES HEREUNDER ARE ESTIMATED ON THE BASIS OF A 4-HOUR EXPOSURE. Acute oral toxicity (LD50): 316 mg/kg [Mouse]. Acute toxicity of the vapor (LD50): 9500 ppm 4 hour(s) [Mouse].

CHRONIC EFFECTS ON HUMANS: CARCINOGENIC EFFECTS: Classified + (PROVEN) by OSHA. Classified 2B (Possible for human.) by IARC. A4 (Not classifiable for human or animal). By ACGIH. The substance is toxic to the nervous system, upper respiratory tract.

OTHER TOXIC EFFECTS ON HUMANS: Hazardous in case of skin contact (irritant, permeator), of ingestion, of inhalation.

SPECIAL REMARKS ON TOXICITY TO ANIMALS: Not available.

SPECIAL REMARKS ON CHRONIC EFFECTS ON HUMANS: Animal embryotoxic. Postnasal development injury in animal. Menstrual disorders in human. Human: passes the placental barrier, detected in maternal milk.

SPECIAL REMARKS ON OTHER TOXIC EFFECTS ON HUMANS: Not available.

ECOLOGICAL INFORMATION

ECOTOXICITY: Not available.

BOD5 AND COD: Not available.

PRODUCTS OF BIODEGRADATION:

Possibly hazardous short-term degradation products are not likely. However, long-term degradation products may arise.

TOXICITY OF THE PRODUCTS OF BIODEGRADATION: The products of degradation are more toxic.

SPECIAL REMARKS ON THE PRODUCTS OF BIODEGRADATION: Not available.

DISPOSAL CONSIDERATIONS

WASTE DISPOSAL: Consult your local or regional authorities.

TRANSPORT INFORMATION

DOT CLASSIFICATION: Class 3: Flammable liquid.

IDENTIFICATION: Styrene monomer, inhibited: UN2055 PG: III

SPECIAL PROVISIONS FOR TRANSPORT: Marine Pollutant

OTHER REGULATORY INFORMATION

FEDERAL AND STATE REGULATIONS: Pennsylvania RTK: Styrene (monomer) Florida: Styrene (monomer) Minnesota: Styrene (monomer) Massachusetts RTK: Styrene (monomer) New Jersey: Styrene (monomer) TSCA 8(b) inventory: Styrene (monomer) SARA 313 toxic chemical notification and release reporting: Styrene (monomer) CERCLA: Hazardous substances: Styrene (monomer).

OTHER REGULATIONS: OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200).

OTHER CLASSIFICATIONS: WHMIS (CANADA): CLASS B-2: Flammable liquid with a flash point lower than 37.8°C (100°F). **CLASS D-2A:** Material causing other toxic effects (VERY TOXIC).

DSCL (EEC): R-10- Flammable. R38 – Irritating to skin. R41 – Risk of serious damage to eyes. R45 – may cause cancer..

HMIS (U.S.A.):

HEALTH HAZARD: 2
FIRE HAZARD: 3
REACTIVITY: 0
PERSONAL PROTECTION: 0

NATIONAL FIRE PROTECTION ASSOCIATION (U.S.A.)

HEALTH: 2
FLAMMABILITY: 3
REACTIVITY: 2
SPECIFIC HAZARD:

PROTECTIVE EQUIPMENT: Gloves. Lab coat. Vapor respirator. Be sure to use an approved/certified respirator or equivalent. Wear appropriate respirator when ventilation is inadequate. Splash goggles

OTHER REGULATORY INFORMATION

REFERENCES: Not available.

OTHER SPECIAL CONSIDERATIONS: Not available.

Created: 10/09/05

Last Updated: 9/24/10

Verified and Printed: 12/21/10

The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty or merchantability of any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes. In no event shall EMS be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential or exemplary damages, however arising, even if EMS has been advised of the possibility of such damages.