Printing date 02/01/2023 Reviewed on 02/01/2023

### 1 Identification

· Product identifier

· Trade name: LiteFix liquid

· Article number: 1259-L

· Application of the substance / the mixture Laboratory chemicals

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

Electron Microscopy Sciences

1560 Industry Road

USA-Hatfield, PA 19440

Tel: 215-412-8400 Fax: 215-412-8450

email: in fo@ems diasum.com

www.emsdiasum.com

· Information department: Product safety department

· Emergency telephone number:

ChemTrec 1-800-424-9300 Contract CCN7661

1-703-527-3887

## 2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flammable Liquids 2

H225 Highly flammable liquid and vapor.



Skin Irritation 2

H315 Causes skin irritation.

Sensitization - Skin 1

H317 May cause an allergic skin reaction.

Specific Target Organ Toxicity - Single Exposure 3 H335 May cause respiratory irritation.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms





GHS02

GHS07

- · Signal word Danger
- · Hazard-determining components of labeling:

Methyl Methacrylate

tetramethylene dimethacrylate

· Hazard statements

Highly flammable liquid and vapor.

Causes skin irritation.

May cause an allergic skin reaction.

May cause respiratory irritation.

(Contd. on page 2)

Printing date 02/01/2023 Reviewed on 02/01/2023

Trade name: LiteFix liquid

(Contd. of page 1)

#### · Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

*Use only non-sparking tools.* 

Take precautionary measures against static discharge.

Avoid breathing dust/fume/gas/mist/vapors/spray

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Call a poison center/doctor if you feel unwell.

Specific treatment (see on this label).

Take off contaminated clothing and wash it before reuse.

If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

In case of fire: Use CO2, powder or water spray to extinguish.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 1 Fire = 3Reactivity = 0

· HMIS-ratings (scale 0 - 4)



- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

### 3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

	· Dangerous	components:	
ſ	80-62-6	Methyl Methacrylate	>50-≤100%
Ī	2082-81-7	tetramethylene dimethacrylate	>2.5- <i>≤</i> 10%

-US

Printing date 02/01/2023 Reviewed on 02/01/2023

Trade name: LiteFix liquid

(Contd. of page 2)

### 4 First-aid measures

- · Description of first aid measures
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

*In case of unconsciousness place patient stably in side position for transportation.* 

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

### 5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

### 6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

· PAC-1:	
80-62-6 Methyl Methacrylate	17 ppm
· PAC-2:	
80-62-6 Methyl Methacrylate	120 ppm
· PAC-3:	
80-62-6 Methyl Methacrylate	570 ppm

### 7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

(Contd. on page 4)

Printing date 02/01/2023 Reviewed on 02/01/2023

Trade name: LiteFix liquid

(Contd. of page 3)

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· Specific end use(s) No further relevant information available.

## 8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.

At this time, the remaining constituent has no known exposure limits.

#### 80-62-6 Methyl Methacrylate

PEL Long-term value: 410 mg/m³, 100 ppm REL Long-term value: 410 mg/m³, 100 ppm

TLV Short-term value: 100 ppm Long-term value: 50 ppm

DSEN, A4

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

(Contd. on page 5)

Printing date 02/01/2023 Reviewed on 02/01/2023

Trade name: LiteFix liquid

· Material of gloves

(Contd. of page 4)

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

· Partition coefficient (n-octanol/water): Not determined.

O DI					,	
9 Ph	vsical	and	C	remical	nro	nerties
- 1 IV		with	-	<i>tollitted</i>	י עועי	

· Information on basic physical and c	hemical properties
· General Information	
· Appearance:	** **
Form:	Liquid
Color:	Colorless
· Odor:	Ester-like
· Odor threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	101 °C (213.8 °F)
· Flash point:	10 °C (50 °F)
· Flammability (solid, gaseous):	Highly flammable.
· Ignition temperature:	430 °C (806 °F)
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· Explosion limits:	
Lower:	2.1 Vol %
Upper:	12.5 Vol %
· Vapor pressure at 20 °C (68 °F):	47 hPa (35.3 mm Hg)
· Density at 20 °C (68 °F):	0.945 g/cm³ (7.88603 lbs/gal)
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.

(Contd. on page 6)

Printing date 02/01/2023 Reviewed on 02/01/2023

Trade name: LiteFix liquid

	(Contd. of page
· Viscosity: Dynamic: Kinematic:	Not determined. Not determined.
· Solvent content: VOC content:	0.00 % 0.0 g/l / 0.00 lb/gal
Solids content:	0.0 %
· Other information	No further relevant information available.

### 10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

## 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: No irritating effect.
- · Sensitization: Sensitization possible through skin contact.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

· Carcinogenic categories

$\cdot IA$	RC	(I	nter	na	ıtione	ıl A	Agency	for	Research	on	Cancer)
0.0		-		-		-					

80-62-6 Methyl Methacrylate

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety Health Administration)

None of the ingredients is listed.

### 12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.

(Contd. on page 7)

3

Printing date 02/01/2023 Reviewed on 02/01/2023

Trade name: LiteFix liquid

(Contd. of page 6)

- · Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

## 13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

· Label

· Packing group

· DOT, ADR, IMDG, IATA
· Environmental hazards:

· Special precautions for user

· Hazard identification number (Kemler code): 33

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

UN-Number	
DOT, ADR, IMDG, IATA	UN1247
UN proper shipping name	
DOT	Methyl methacrylate monomer, stabilized mixture
ADR	1247 METHYL METHACRYLATE MONOMER, STABILIZE mixture
IMDG, IATA	METHYL METHACRYLATE MONOMER, STABILIZED mixture
PARIMAT (CITE)	
Class	3 Flammable liquids
Label	3
ADR, IMDG, IATA	
Class	3 Flammable liquids

Not applicable.

Warning: Flammable liquids

(Contd. on page 8)

Printing date 02/01/2023 Reviewed on 02/01/2023

Trade name: LiteFix liquid

	(Contd. of page					
EMS Number:	F-E,S-D					
Stowage Category	C					
· Stowage Code	SW1 Protected from sources of heat.					
	SW2 Clear of living quarters.					
Transport in bulk according to Annex II of						
MARPOL73/78 and the IBC Code	Not applicable.					
Transport/Additional information:						
DOT						
· Quantity limitations	On passenger aircraft/rail: 5 L					
	On cargo aircraft only: 60 L					
· <i>ADR</i>						
Excepted quantities (EQ)	Code: E2					
	Maximum net quantity per inner packaging: 30 ml					
	Maximum net quantity per outer packaging: 500 ml					
· IMDG						
· Limited quantities (LQ)	IL					
Excepted quantities (EQ)	Code: E2					
	Maximum net quantity per inner packaging: 30 ml					
	Maximum net quantity per outer packaging: 500 ml					
· UN ''Model Regulation'':	UN 1247 METHYL METHACRYLATE MONOMER, STABILIZE					
3	MIXTURE. 3. II					

### 15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.
- Sara
- · Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

80-62-6 Methyl Methacrylate

· TSCA (Toxic Substances Control Act):

All components have the value ACTIVE.

· Hazardous Air Pollutants

80-62-6 Methyl Methacrylate

- · Proposition 65
- · Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

(Contd. on page 9)

Printing date 02/01/2023 Reviewed on 02/01/2023

Trade name: LiteFix liquid

(Contd. of page 8)

· Carcinogenic categories

· EPA (Environmental Protection Agency)

80-62-6 Methyl Methacrylate

E, NL

· TLV (Threshold Limit Value)

80-62-6 Methyl Methacrylate

A4

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms





- · Signal word Danger
- · Hazard-determining components of labeling:

Methyl Methacrylate

tetramethylene dimethacrylate

· Hazard statements

Highly flammable liquid and vapor.

Causes skin irritation.

May cause an allergic skin reaction.

May cause respiratory irritation.

· Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

*Use explosion-proof electrical/ventilating/lighting/equipment.* 

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust/fume/gas/mist/vapors/spray

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Call a poison center/doctor if you feel unwell.

Specific treatment (see on this label).

Take off contaminated clothing and wash it before reuse.

If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

In case of fire: Use CO2, powder or water spray to extinguish.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

Printing date 02/01/2023 Reviewed on 02/01/2023

Trade name: LiteFix liquid

(Contd. of page 9)

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Contact.
- · Date of preparation / last revision 02/01/2023
- · Abbreviations and acronyms:

 $ADR: Accord\ relatif\ au\ transport\ international\ des\ marchandises\ dangereuses\ par\ route\ (European\ Agreement\ Concerning\ the\ International\ Concerning\ the\ Concern$ 

Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

 $DOT: \ US \ Department \ of \ Transportation$ 

 ${\it IATA: International Air Transport Association}$ 

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU) PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety Health
TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit

Flammable Liquids 2: Flammable liquids – Category 2 Skin Irritation 2: Skin corrosion/irritation – Category 2 Sensitization - Skin 1: Skin sensitisation – Category 1

Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) - Category 3

US