Printing date 01/17/2023

Reviewed on 01/17/2023

## **1** Identification

- · Product identifier
- · Trade name: Mikrostik Adhesive, Non-Conductive
- · Article number: 12646-01
- · Application of the substance / the mixture Laboratory chemicals
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier: Electron Microscopy Sciences 1560 Industry Road USA-Hatfield, PA 19440 Tel: 215-412-8400 Fax: 215-412-8450 email: info@emsdiasum.com www.emsdiasum.com
- · Information department: Product safety department · Emergency telephone number: ChemTrec 1-800-424-9300 Contract CCN7661 1-703-527-3887

## 2 Hazard(s) identification

· Classification of the substance or mixture



Flammable Liquids 2

GHS08 Health hazard

Sensitization - Respiratory 1

Toxic to Reproduction 2

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled. H361 Suspected of damaging fertility or the unborn child. Specific Target Organ Toxicity - Repeated Exposure 2 H373 May cause damage to organs through prolonged or repeated exposure.

H225 Highly flammable liquid and vapor.



Acute Toxicity - Oral 4 H302 Harmful if swallowed. Eye Irritation 2A H319 Causes serious eye irritation. Specific Target Organ Toxicity - Single Exposure 3 H336 May cause drowsiness or dizziness.

· Label elements

• GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS). · Hazard pictograms



(Contd. on page 2)

US

Printing date 01/17/2023

Reviewed on 01/17/2023

Trade name: Mikrostik Adhesive, Non-Conductive

Signal word Danger	(Contd. of page
Hazard-determining components of labeling:	
METHYL ETHYL KETONE	
toluene	
Hazard statements	
Highly flammable liquid and vapor.	
Harmful if swallowed.	
Causes serious eye irritation.	
May cause allergy or asthma symptoms or breathing difficulties if inhaled.	
Suspected of damaging fertility or the unborn child.	
May cause drowsiness or dizziness.	
May cause damage to organs through prolonged or repeated exposure.	
Precautionary statements	
Obtain special instructions before use.	
Do not handle until all safety precautions have been read and understood.	
Keep away from heat/sparks/open flames/hot surfaces No smoking.	
Ground/bond container and receiving equipment.	
Use explosion-proof electrical/ventilating/lighting/equipment.	
Use only non-sparking tools.	
Take precautionary measures against static discharge.	
Do not breathe dust/fume/gas/mist/vapors/spray.	
Wash thoroughly after handling.	
Do not eat, drink or smoke when using this product.	
Use only outdoors or in a well-ventilated area.	
Wear protective gloves/protective clothing/eye protection/face protection.	
[In case of inadequate ventilation] wear respiratory protection.	
If swallowed: Call a poison center/doctor if you feel unwell.	
Rinse mouth.	
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shov	ver.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.	
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if press	ent and easy to d
Continue rinsing.	
IF exposed or concerned: Get medical advice/attention.	
Get medical advice/attention if you feel unwell.	
If eye irritation persists: Get medical advice/attention.	
If experiencing respiratory symptoms: Call a poison center/doctor.	
In case of fire: Use CO2, powder or water spray to extinguish.	
Store in a well-ventilated place. Keep container tightly closed.	
Store in a well-ventilated place. Keep cool.	
Store locked up.	
Dispose of contents/container in accordance with local/regional/national/international regulat	ions.
Classification system:	
NFPA ratings (scale 0 - 4)	
Health = 2	
$\frac{3}{Fire = 3}$	
$\frac{2}{Reactivity} = 0$	
HMIS-ratings (scale 0 - 4)	
<b>HEALTH</b> 2 $Health = 2$	
FIRE 3 $Fire = 3$	
<b>REACTIVITY</b> Reactivity = $0$	

 $(Contd. \ on \ page \ 3)$ 

US

Printing date 01/17/2023

Reviewed on 01/17/2023

#### Trade name: Mikrostik Adhesive, Non-Conductive

(Contd. of page 2)

- Other hazards
- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

## 3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- Description: Mixture of the substances listed below with nonhazardous additions.
- · Dangerous components:

78-9 <i>3-3</i>	METHYL ETHYL KETONE	>50- <i>≤</i> 100%
110-19-0	isobutyl acetate	>2.5- <i>≤</i> 10%
108-88-3	toluene	>2.5- <i>≤</i> 10%

### 4 First-aid measures

#### · Description of first aid measures

• General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Generally the product does not irritate the skin.
- After eye contact:
- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- · After swallowing: Immediately call a doctor.
- · Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

## **5** Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:
- CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

## 6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- *Environmental precautions:* Dilute with plenty of water.
- Do not allow to enter sewers/ surface or ground water.
- *Methods and material for containment and cleaning up:* Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13.

(Contd. on page 4)

US

Printing date 01/17/2023

Reviewed on 01/17/2023

### Trade name: Mikrostik Adhesive, Non-Conductive

<b>F</b> 1		(Contd. of page 3)
	equate ventilation.	
	to other sections	
	n 7 for information on safe handling.	
	a 8 for information on personal protection equipment.	
	n 13 for disposal information.	
· Protective	Action Criteria for Chemicals	
· PAC-1:		
78-93-3	METHYL ETHYL KETONE	200 ppm
9002-86-2	polyvinyl chloride	3 mg/m <sup>3</sup>
110-19-0	isobutyl acetate	450 ppm
108-88-3	toluene	67 ppm
· PAC-2:		
78-93-3	METHYL ETHYL KETONE	2700* ppm
9002-86-2	polyvinyl chloride	33 mg/m <sup>3</sup>
110-19-0	isobutyl acetate	1300* ppm
108-88-3	toluene	560 ppm
· PAC-3:		
78-93-3	METHYL ETHYL KETONE	4000* ppm
9002-86-2	polyvinyl chloride	200 mg/m <sup>3</sup>
110-19-0	isobutyl acetate	7500** ppm
108-88-3	toluene	3700* ppm

## 7 Handling and storage

· Handling:

- Precautions for safe handling Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
   Information about protection against explosions and fires: Keep ignition sources away - Do not smoke.
- Protect from heat.

Protect against electrostatic charges.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:
- Keep receptacle tightly sealed.
- Store in cool, dry conditions in well sealed receptacles.
- Protect from heat and direct sunlight.
- Specific end use(s) No further relevant information available.

# 8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see item 7.

(Contd. on page 5)

<sup>-</sup> US

Printing date 01/17/2023

Reviewed on 01/17/2023

## Trade name: Mikrostik Adhesive, Non-Conductive

	(Contd. of page 4
· Cont	trol parameters
· Com	ponents with limit values that require monitoring at the workplace:
78-9	3-3 METHYL ETHYL KETONE
PEL	Long-term value: 590 mg/m <sup>3</sup> , 200 ppm
REL	Short-term value: 885 mg/m <sup>3</sup> , 300 ppm
	Long-term value: 590 mg/m <sup>3</sup> , 200 ppm
TLV	Short-term value: 300 ppm
	Long-term value: 200 ppm
	BEI
110-	19-0 isobutyl acetate
PEL	Long-term value: 700 mg/m <sup>3</sup> , 150 ppm
REL	Long-term value: 700 mg/m³, 150 ppm
TLV	Short-term value: 150 ppm
	Long-term value: 50 ppm
108-	88-3 toluene
PEL	Long-term value: 200 ppm
	Ceiling limit value: 300; 500* ppm
	*10-min peak per 8-hr shift
REL	Short-term value: 560 mg/m <sup>3</sup> , 150 ppm
	Long-term value: 375 mg/m³, 100 ppm
TLV	Long-term value: 20 ppm
	BEI, OTO, A4
-	edients with biological limit values:
	3-3 METHYL ETHYL KETONE
BEI	2 mg/L
	Medium: urine
	Time: end of shift Parameter: Methyl ethyl ketone (nonspecific)
108	88-3 toluene
BEI	0.02 mg/L Medium: blood
	Time: prior to last shift of workweek
	Parameter: Toluene
	0.03 mg/L
	Medium: urine
	Time: end of shift
	Parameter: Toluene
	0.3 mg/g creatinine
	Medium: urine
	Time: end of shift
	Parameter: o-Cresol with hydrolysis (background)
· Addi	itional information: The lists that were valid during the creation were used as basis.
·Ern	osure controls
	onal protective equipment:

Personal protective equipment:
General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

(Contd. on page 6)

US

Printing date 01/17/2023

Reviewed on 01/17/2023

#### Trade name: Mikrostik Adhesive, Non-Conductive

(Contd. of page 5)

Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Avoid contact with the eyes. Avoid contact with the eyes and skin.

### · Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

#### · Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

#### · Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:



Tightly sealed goggles

Information on basic physical and General Information	chemical properties
Appearance:	
Form:	Liquid
Color:	Clear
Odor:	Pungent
Odor threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	79 °C (174.2 °F)
Flash point:	-6 °C (21.2 °F)
Flammability (solid, gaseous):	Highly flammable.
Ignition temperature:	405 °C (761 °F)
Decomposition temperature:	Not determined.
Auto igniting:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapo mixtures are possible.
Explosion limits:	
Lower:	1.8 Vol %

Printing date 01/17/2023

Reviewed on 01/17/2023

### Trade name: Mikrostik Adhesive, Non-Conductive

		(Contd. of page 6
Upper:	11.5 Vol %	
· Vapor pressure at 20 °C (68 °F):	105 hPa (78.8 mm Hg)	
Density at 20 °C (68 °F):	0.85 g/cm <sup>3</sup> (7.09325 lbs/gal)	
· Relative density	Not determined.	
· Vapor density	Not determined.	
· Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
Water:	Fully miscible.	
Partition coefficient (n-octanol/wate	r): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
Solvent content:		
Organic solvents:	87.0 %	
VOC content:	87.00 %	
	739.5 g/l / 6.17 lb/gal	
Solids content:	0.0 %	
Other information	No further relevant information available.	

# **10 Stability and reactivity**

• *Reactivity* No further relevant information available.

- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

# **11** Toxicological information

#### · Information on toxicological effects

• Acute toxicity:

· LD/LC50 values that are relevant for classification:

78-93-3 METHYL ETHYL KETONE

*Oral LD50 3,300 mg/kg (rat)* 

Dermal LD50 5,000 mg/kg (rabbit)

#### · Primary irritant effect:

- on the skin: No irritant effect.
- on the eye: Irritating effect.
- · Sensitization: Sensitization possible through inhalation.
- · Additional toxicological information:
- The product shows the following dangers according to internally approved calculation methods for preparations: Harmful

Irritant

(Contd. on page 8)

Printing date 01/17/2023

Reviewed on 01/17/2023

#### Trade name: Mikrostik Adhesive, Non-Conductive

(Contd. of page 7)

3

3

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

9002-86-2 polyvinyl chloride

108-88-3 toluene

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety Health Administration)

None of the ingredients is listed.

## **12** Ecological information

· Toxicity

- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:

· General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- · Other adverse effects No further relevant information available.

## **13 Disposal considerations**

· Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- $\cdot \textit{Recommendation: Disposal must be made according to official regulations.}$
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

· UN-Number · DOT, ADR, IMDG, IATA	UN1993
· UN proper shipping name	
$\cdot DOT$	Flammable liquids, n.o.s. (Ethyl methyl ketone)
·ADR	1993 FLAMMABLE LIQUID, N.O.S. (ETHYL METHYL KETONI
	(METHYL ETHYL KETONE))
· IMDG, IATA	FLAMMABLE LIQUID, N.O.S. (ETHYL METHYL KETONE
	(METHYL ETHYL KETONE))

Printing date 01/17/2023

Reviewed on 01/17/2023

Trade name: Mikrostik Adhesive, Non-Conductive

	(Contd. of page
· Transport hazard class(es)	
·DOT	
PRAME FUCT	
· Class	3 Flammable liquids
· Label	3
· ADR, IMDG, IATA	
· Class	3 Flammable liquids
· Label	3
· Packing group	
· DOT, ADR, IMDG, IATA	III
· Environmental hazards:	Not applicable.
· Special precautions for user	Warning: Flammable liquids
• Hazard identification number (Kemler code)	
· EMS Number: · Stowage Category	F-E, <u>S-E</u> B
• Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
·DOT	
· Quantity limitations	On passenger aircraft/rail: 5 L
	On cargo aircraft only: 60 L
· ADR	
$\cdot$ Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per uner packaging: 50 ml Maximum net quantity per outer packaging: 1000 ml
· IMDG	
· Limited quantities (LQ)	1L
$\cdot$ Excepted quantities ( $\widetilde{EQ}$ )	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
• UN "Model Regulation":	UN 1993 FLAMMABLE LIQUID, N.O.S. (ETHYL METHY KETONE (METHYL ETHYL KETONE)), 3, III

# **15 Regulatory information**

• Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.

(Contd. on page 10)

US

Printing date 01/17/2023

Reviewed on 01/17/2023

### Trade name: Mikrostik Adhesive, Non-Conductive

· Sara	(Contd. of page 9)
Section 355 (extremely hazardous substances):	
None of the ingredients is listed.	
• Section 313 (Specific toxic chemical listings):	
108-88-3 toluene	
· TSCA (Toxic Substances Control Act):	
All components have the value ACTIVE.	
Hazardous Air Pollutants	
108-88-3 toluene	
Proposition 65	
· Chemicals known to cause cancer:	
None of the ingredients is listed.	
Chemicals known to cause reproductive toxicity for females:	
None of the ingredients is listed.	
Chemicals known to cause reproductive toxicity for males:	
None of the ingredients is listed.	
· Chemicals known to cause developmental toxicity:	
108-88-3 toluene	
· Carcinogenic categories	
• EPA (Environmental Protection Agency)	

$\cdot EPA$ (Env	ironmental Protection Agency)	
78-93-3	METHYL ETHYL KETONE	Ι
108-88-3	toluene	II
• TLV (Thre	eshold Limit Value)	
9002-86-2	polyvinyl chloride	A4
108-88-3	toluene .	A4
· NIOSH-Ca (National Institute for Occupational Safety and Health)		

None of the ingredients is listed.

• *GHS label elements* The product is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms* 



· Signal word Danger

Hazard-determining components of labeling: METHYL ETHYL KETONE toluene
Hazard statements Highly flammable liquid and vapor. Harmful if swallowed. Causes serious eye irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled. Suspected of damaging fertility or the unborn child. May cause drowsiness or dizziness.

(Contd. on page 11)

US

Printing date 01/17/2023

Reviewed on 01/17/2023

## Trade name: Mikrostik Adhesive, Non-Conductive

	(Contd. of page 10)
May cause damage to organs through prolonged or repeated exposure.	
Precautionary statements	
Obtain special instructions before use.	
Do not handle until all safety precautions have been read and understood.	
Keep away from heat/sparks/open flames/hot surfaces No smoking.	
Ground/bond container and receiving equipment.	
Use explosion-proof electrical/ventilating/lighting/equipment.	
Use only non-sparking tools.	
Take precautionary measures against static discharge.	
Do not breathe dust/fume/gas/mist/vapors/spray.	
Wash thoroughly after handling.	
Do not eat, drink or smoke when using this product.	
Use only outdoors or in a well-ventilated area.	
Wear protective gloves/protective clothing/eye protection/face protection.	
[In case of inadequate ventilation] wear respiratory protection.	
If swallowed: Call a poison center/doctor if you feel unwell.	
Rinse mouth.	
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/	shower.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.	
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if p Continue rinsing.	present and easy to do.
IF exposed or concerned: Get medical advice/attention.	
Get medical advice/attention if you feel unwell.	
If eye irritation persists: Get medical advice/attention.	
If experiencing respiratory symptoms: Call a poison center/doctor.	
In case of fire: Use CO2, powder or water spray to extinguish.	
Store in a well-ventilated place. Keep container tightly closed.	
Store in a well-ventilated place. Keep cool.	
Store locked up.	1
Dispose of contents/container in accordance with local/regional/national/international reg	guiations.
Chemical safety assessment: A Chemical Safety Assessment has not been carried out.	

# **16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Contact:

eonmen.
• Date of preparation / last revision 01/17/2023
· Abbreviations and acronyms:
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International
Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
DOT: US Department of Transportation
IATA: International Air Transport Association
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
NIOSH: National Institute for Occupational Safety
OSHA: Occupational Safety Health
TLV: Threshold Limit Value
(Contd. on page 12)

Printing date 01/17/2023

Reviewed on 01/17/2023

#### Trade name: Mikrostik Adhesive, Non-Conductive

(Contd. of page 11)

PEL: Permissible Exposure Limit REL: Recommended Exposure Limit BEI: Biological Exposure Limit Flammable Liquids 2: Flammable liquids – Category 2 Acute Toxicity - Oral 4: Acute toxicity – Category 4 Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A Sensitization - Respiratory 1: Respiratory sensitisation – Category 1 Toxic to Reproduction 2: Reproductive toxicity – Category 2 Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) – Category 3 Specific Target Organ Toxicity - Repeated Exposure 2: Specific target organ toxicity (repeated exposure) – Category 2