Printing date 11/04/2022 Reviewed on 11/04/2022

#### 1 Identification

· Product identifier

· Trade name: EUKITT Neo Xylene Free Mounting Medium

· Article number: 15320-20, 15322-20

· Application of the substance / the mixture Laboratory chemicals

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

Electron Microscopy Sciences

1560 Industry Road USA-Hatfield, PA 19440

Tel: 215-412-8400 Fax: 215-412-8450

email: info@emsdiasum.com

www.emsdiasum.com

· Information department: Product safety department

· Emergency telephone number:

ChemTrec 1-800-424-9300 Contract CCN7661

1-703-527-3887

#### 2 Hazard(s) identification

· Classification of the substance or mixture



Skin Irrititation 2 H315 Causes skin irritation.

Sensitization - Skin 1 H317 May cause an allergic skin reaction.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms



GHS07

- · Signal word Warning
- · Hazard-determining components of labeling:

(R)-p-mentha-1,8-diene

Methyl Methacrylate

N-BUTYL METHACRYLATE, MONOMER

· Hazard statements

Causes skin irritation.

May cause an allergic skin reaction.

· Precautionary statements

Avoid breathing dust/fume/gas/mist/vapors/spray

Wash thoroughly after handling.

Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves.

If on skin: Wash with plenty of water.

*Take off contaminated clothing and wash it before reuse.* 

If skin irritation or rash occurs: Get medical advice/attention.

Specific treatment (see on this label).

(Contd. on page 2)

Printing date 11/04/2022 Reviewed on 11/04/2022

#### Trade name: EUKITT Neo Xylene Free Mounting Medium

(Contd. of page 1)

Wash contaminated clothing before reuse.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 1Fire = 0Reactivity = 0

· HMIS-ratings (scale 0 - 4)



1 Health = 1 Fire = 0

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

### 3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · **Description:** Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:		
5989-27-5	(R)-p-mentha-1,8-diene	>50-≤100%
80-62-6	Methyl Methacrylate	<i>≤</i> 2.5%
	N-BUTYL METHACRYLATE, MONOMER	<i>≤</i> 2.5%

#### 4 First-aid measures

- · Description of first aid measures
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

#### 5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- · Special hazards arising from the substance or mixture No further relevant information available.

(Contd. on page 3)

Printing date 11/04/2022 Reviewed on 11/04/2022

Trade name: EUKITT Neo Xylene Free Mounting Medium

(Contd. of page 2)

- · Advice for firefighters
- · Protective equipment: No special measures required.

#### 6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures Not required.
- · Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

· PAC-1:		
5989-27-5	(R)-p-mentha-1,8-diene	15 ppm
80-62-6	Methyl Methacrylate	17 ppm
	N-BUTYL METHACRYLATE, MONOMER	19 mg/m³
· PAC-2:		
5989-27-5	(R)-p-mentha-1,8-diene	67 ppm
80-62-6	Methyl Methacrylate	120 ррт
	N-BUTYL METHACRYLATE, MONOMER	210 mg/m³
· PAC-3:		
5989-27-5	(R)-p-mentha-1,8-diene	170 ppm
80-62-6	Methyl Methacrylate	570 ppm
	N-BUTYL METHACRYLATE, MONOMER	$1,300 \text{ mg/m}^3$

#### 7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

- · Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: None.
- · Specific end use(s) No further relevant information available.

### 8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see item 7.

(Contd. on page 4)

Printing date 11/04/2022 Reviewed on 11/04/2022

Trade name: EUKITT Neo Xylene Free Mounting Medium

(Contd. of page 3)

#### · Control parameters

#### · Components with limit values that require monitoring at the workplace:

The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

#### 80-62-6 Methyl Methacrylate

PEL Long-term value: 410 mg/m³, 100 ppm REL Long-term value: 410 mg/m³, 100 ppm

TLV Short-term value: 100 ppm Long-term value: 50 ppm

DSEN, A4

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection: Goggles recommended during refilling.

#### 9 Physical and chemical properties

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Fluid

*Color:* According to product specification

· Odor: Characteristic

(Contd. on page 5)

Printing date 11/04/2022 Reviewed on 11/04/2022

Trade name: EUKITT Neo Xylene Free Mounting Medium

	(Contd. of pa
· Odor threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	Undetermined.
Flash point:	Not applicable.
Flammability (solid, gaseous):	Not flammable.
Ignition temperature:	255 °C (491 °F)
Decomposition temperature:	Not determined.
Auto igniting:	Product is not selfigniting.
Danger of explosion:	Product does not present an explosion hazard.
Explosion limits:	
Lower:	0.7 Vol %
Upper:	6.1 Vol %
Vapor pressure at 20 $^{\circ}$ C (68 $^{\circ}$ F):	2.3 hPa (1.7 mm Hg)
Density:	Not determined.
· Relative density	Not determined.
Vapor density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.
Partition coefficient (n-octanol/wate	r): Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	80.0 %
VOC content:	80.00 %
	800.0 g/l / 6.68 lb/gal
Solids content:	0.0 %
Other information	No further relevant information available.

### 10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

Printing date 11/04/2022 Reviewed on 11/04/2022

Trade name: EUKITT Neo Xylene Free Mounting Medium

(Contd. of page 5)

### 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: No irritating effect.
- · Sensitization: Sensitization possible through skin contact.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

· Carcinogenic categories

carentos	care into genite caregories		
· IARC (In	· IARC (International Agency for Research on Cancer)		
5989-27-	5 (R)-p-mentha-1,8-diene	3	
80-62-	6 Methyl Methacrylate	3	
· NTP (Na	· NTP (National Toxicology Program)		
None of	None of the ingredients is listed.		
· OSHA-C	· OSHA-Ca (Occupational Safety Health Administration)		
None of	None of the ingredients is listed.		

### 12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Very toxic for fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Very toxic for aquatic organisms

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

#### 13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 7)

Printing date 11/04/2022 Reviewed on 11/04/2022

Trade name: EUKITT Neo Xylene Free Mounting Medium

(Contd. of page 6)

· Uncleaned packagings:

· Recommendation: Disposal must be made according to official regulations.

UN-Number	1112052
DOT, ADR, IMDG, IATA	UN2052
UN proper shipping name	
DOT	Dipentene
ADR	2052 DIPENTENE, ENVIRONMENTALLY HAZARDOUS
<i>IMDG</i>	DIPENTENE, MARINE POLLUTANT
IATA	DIPENTENE
Transport hazard class(es)	
DOT, ADR, IMDG	
Class	3 Flammable liquids

· Class	3 Flammable liqui
· Label	9

 $\cdot$  IATA

 $\cdot DOT$ 

· Remarks:

· Quantity limitations



· Class · Label	3 Flammable liquids 9
· Packing group · DOT, ADR, IMDG, IATA	III
· Environmental hazards:	Product contains environmentally hazardous substances: (R)-p-mentha-1,8-diene
· Marine pollutant:	Yes (DOT) Symbol (fish and tree)
· Special marking (ADR):	Symbol (fish and tree)
· Special precautions for user · Hazard identification number (Kemler code	Warning: Flammable liquids ): 90
· EMS Number: · Stowage Category	F-E,S-E A
· Transport in bulk according to Annex II of	А
MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	

On passenger aircraft/rail: No limit On cargo aircraft only: No limit

Special marking with the symbol (fish and tree).

(Contd. on page 8)

Printing date 11/04/2022 Reviewed on 11/04/2022

Trade name: EUKITT Neo Xylene Free Mounting Medium

(Contd. of page 7)  $\cdot ADR$ Code: E1 · Excepted quantities (EQ) Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml · IMDG · Limited quantities (LQ) 5L· Excepted quantities (EQ) Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml · UN "Model Regulation": UN 2052 DIPENTENE, 9, III, ENVIRONMENTALLY **HAZARDOUS** 

#### 15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.
- · Sara
- · Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

80-62-6 Methyl Methacrylate

· TSCA (Toxic Substances Control Act):

All components have the value ACTIVE.

· Hazardous Air Pollutants

80-62-6 Methyl Methacrylate

- · Proposition 65
- · Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

- · Carcinogenic categories
- · EPA (Environmental Protection Agency)

80-62-6 Methyl Methacrylate

E, NL

· TLV (Threshold Limit Value)

80-62-6 Methyl Methacrylate

A4

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 9)

(Contd. of page 8)

## Safety Data Sheet acc. to OSHA HCS

Printing date 11/04/2022 Reviewed on 11/04/2022

#### Trade name: EUKITT Neo Xylene Free Mounting Medium

· Hazard pictograms



· Signal word Warning

#### · Hazard-determining components of labeling:

(R)-p-mentha-1,8-diene

Methyl Methacrylate

N-BUTYL METHACRYLATE, MONOMER

· Hazard statements

Causes skin irritation.

May cause an allergic skin reaction.

· Precautionary statements

Avoid breathing dust/fume/gas/mist/vapors/spray

Wash thoroughly after handling.

Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves.

If on skin: Wash with plenty of water.

Take off contaminated clothing and wash it before reuse.

If skin irritation or rash occurs: Get medical advice/attention.

Specific treatment (see on this label).

Wash contaminated clothing before reuse.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Contact:
- · Date of preparation / last revision 11/04/2022 / -
- · Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Skin Irrititation 2: Skin corrosion/irritation – Category 2 Sensitization - Skin 1: Skin sensitisation – Category 1

US