Printing date 05/03/2022 Reviewed on 05/03/2022

1 Identification

- · Product identifier
- · Trade name: DIFFERENTIAL QUIK III FIXATIVE
- · Article number: 26096-25(A), 26096-50(A), 26096-75(A)
- · Application of the substance / the mixture Laboratory chemicals
- Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

Electron Microscopy Sciences

1560 Industry Road

USA-Hatfield, PA 19440

Tel: 215-412-8400 Fax: 215-412-8450

email: sgkcck@aol.com www.emsdiasum.com

- · Information department: Product safety department
- · Emergency telephone number:

ChemTrec 1-800-424-9300 Contract CCN7661

1-703-527-3887

2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flammable Liquids 2

H225 Highly flammable liquid and vapor.



GHS06 Skull and crossbones

Acute Toxicity - Oral 3

H301 Toxic if swallowed.

Acute Toxicity - Dermal 3

H311 Toxic in contact with skin.



GHS08 Health hazard

Specific Target Organ Toxicity - Single Exposure 1

H370 Causes damage to the central nervous system and the visual organs.

Specific Target Organ Toxicity - Repeated Exposure 2 H373 May cause damage to organs through prolonged or repeated exposure.



Acute Toxicity - Inhalation 4

H332 Harmful if inhaled.

- · Label elements
- GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

 (Contd. on page 2)

-)

(Contd. of page 1)

Safety Data Sheet acc. to OSHA HCS

Printing date 05/03/2022 Reviewed on 05/03/2022

Trade name: DIFFERENTIAL QUIK III FIXATIVE

· Hazard pictograms







· Signal word Danger

· Hazard-determining components of labeling:

Methyl Alcohol

· Hazard statements

Highly flammable liquid and vapor.

Toxic if swallowed or in contact with skin.

Harmful if inhaled.

Causes damage to the central nervous system and the visual organs.

May cause damage to organs through prolonged or repeated exposure.

· Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Immediately call a poison center/doctor.

Specific treatment (see on this label).

Rinse mouth.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF exposed: Call a POISON CENTER or doctor/physician.

Call a poison center/doctor if you feel unwell.

Get medical advice/attention if you feel unwell.

Take off immediately all contaminated clothing and wash it before reuse.

In case of fire: Use CO2, powder or water spray to extinguish.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- Classification system:
- NFPA ratings (scale 0 4)



Health = 1Fire = 3Reactivity = 0

· HMIS-ratings (scale 0 - 4)



*1 Health = *1

Fire = 3

Printing date 05/03/2022 Reviewed on 05/03/2022

Trade name: DIFFERENTIAL QUIK III FIXATIVE

(Contd. of page 2)

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · **Description:** Mixture of the substances listed below with nonhazardous additions.
- · Dangerous components:

67-56-1 Methyl Alcohol

>50-≤100%

4 First-aid measures

- · Description of first aid measures
- · General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

In case of irregular breathing or respiratory arrest provide artificial respiration.

- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: Do not induce vomiting; immediately call for medical help.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions:

Dilute with plenty of water.

Do not allow to enter sewers/surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

(Contd. on page 4)

Reviewed on 05/03/2022 Printing date 05/03/2022

Trade name: DIFFERENTIAL QUIK III FIXATIVE

(Contd. of page 3)

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· PAC-1:	
67-56-1 Methyl Alcohol	530 ppn
PAC-2:	
67-56-1 Methyl Alcohol	2,100 ppi
PAC-3:	
67-56-1 Methyl Alcohol	7200* ppi

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect from heat.

Protect against electrostatic charges.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

· Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.

· Control parameters				
· Components with limit values that require monitoring at the workplace:				
67-56-1 Methyl Alcohol				
Long-term value: 260 mg/m³, 200 ppm				
L Short-term value: 325 mg/m³, 250 ppm				
Long-term value: 260 mg/m³, 200 ppm				

Skin

Short-term value: 250 ppm Long-term value: 200 ppm

Skin; BEI

(Contd. on page 5)

Printing date 05/03/2022 Reviewed on 05/03/2022

Trade name: DIFFERENTIAL QUIK III FIXATIVE

(Contd. of page 4)

· Ingredients with biological limit values:

67-56-1 Methyl Alcohol

BEI 15 mg/L

Medium: urine Time: end of shift

Parameter: Methanol (background, nonspecific)

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

- Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Liquid
Color: Light blue
Odor: Pungent
Odor threshold: Not determined.

(Contd. on page 6)

Printing date 05/03/2022 Reviewed on 05/03/2022

Trade name: DIFFERENTIAL QUIK III FIXATIVE

	(Contd. of page
pH-value:	Not determined.
Change in condition	
Melting point/Melting range:	-98 °C (-144.4 °F)
Boiling point/Boiling range:	64.4 °C (147.9 °F)
Flash point:	9.7 °C (49.5 °F)
Flammability (solid, gaseous):	Not flammable.
Ignition temperature:	385 °C (725 °F)
Decomposition temperature:	Not determined.
Auto igniting:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapo
	mixtures are possible.
Explosion limits:	
Lower:	6 Vol %
Upper:	36 Vol %
Vapor pressure at 20 °C (68 °F):	130.3 hPa (97.7 mm Hg)
Density at 20 °C (68 °F):	0.791 g/cm³ (6.6009 lbs/gal)
Relative density	Not determined.
Vapor density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
Water:	Fully miscible.
Partition coefficient (n-octanol/wate	er): Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	91.0 %
Water:	9.0 %
VOC content:	91.00 %
	775.0 g/l / 6.47 lb/gal
Solids content:	0.0 %
Other information	No further relevant information available.
•	

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.

(Contd. on page 7)

Printing date 05/03/2022 Reviewed on 05/03/2022

Trade name: DIFFERENTIAL QUIK III FIXATIVE

(Contd. of page 6)

· Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC50 values that are relevant for classification:

67-56-1 Methyl Alcohol

 Oral
 LD50
 5,628 mg/kg (rat)

 Dermal
 LD50
 15,800 mg/kg (rabbit)

- Primary irritant effect:
- · on the skin: No irritant effect.
- · on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information: Toxic
- · Carcinogenic categories
- · IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · **vPvB**: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 8)

Printing date 05/03/2022 Reviewed on 05/03/2022

Trade name: DIFFERENTIAL QUIK III FIXATIVE

(Contd. of page 7)

- · Uncleaned packagings:
- Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

Transport information		
· UN-Number		
DOT, ADR, IMDG, IATA	UN1230	
· UN proper shipping name		
· DOT	Methanol solution	
· ADR	1230 METHANOL solution	
· IMDG, IATA	METHANOL solution	
· Transport hazard class(es)		
· DOT		
TOXIC TOXIC		
· Class	3 Flammable liquids	
· Label	3, 6.1	
· ADR		
· Class · Label	3 Flammable liquids 3+6.1	
· IMDG	J + 0.1	
· Class	3 Flammable liquids	
· Label	3/6.1	
· IATA		
· Class	3 Flammable liquids	
· Label	3 (6.1)	
· Packing group · DOT, ADR, IMDG, IATA	II	
· Environmental hazards:	Not applicable.	
· Special precautions for user	Warning: Flammable liquids	
	<u> </u>	(Contd. on page

Printing date 05/03/2022 Reviewed on 05/03/2022

Trade name: DIFFERENTIAL QUIK III FIXATIVE

	(Contd. of pag		
Hazard identification number (Kemler code)	: 336		
EMS Number:	F- E , S - D		
Stowage Category	В		
Stowage Code	SW2 Clear of living quarters.		
Transport in bulk according to Annex II of			
MARPOL73/78 and the IBC Code	Not applicable.		
Transport/Additional information:			
DOT			
Quantity limitations	On passenger aircraft/rail: 1 L		
	On cargo aircraft only: 60 L		
ADR			
Excepted quantities (EQ)	Code: E2		
(- <i>z</i>)	Maximum net quantity per inner packaging: 30 ml		
	Maximum net quantity per outer packaging: 500 ml		
IMDG			
Limited quantities (LQ)	IL		
Excepted quantities (EQ)	Code: E2		
	Maximum net quantity per inner packaging: 30 ml		
	Maximum net quantity per outer packaging: 500 ml		
UN "Model Regulation":	UN 1230 METHANOL SOLUTION, 3 (6.1), II		

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.
- · Sara

· Section 355	(extremel	v hazardous	substances):
---------------	-----------	-------------	--------------

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

67-56-1 Methyl Alcohol

· TSCA (Toxic Substances Control Act):

All components have the value ACTIVE.

· Hazardous Air Pollutants

67-56-1 Methyl Alcohol

· Proposition 65

· Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

67-56-1 Methyl Alcohol

(Contd. on page 10)

Printing date 05/03/2022 Reviewed on 05/03/2022

Trade name: DIFFERENTIAL QUIK III FIXATIVE

(Contd. of page 9)

· Carcinogenic categories

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Threshold Limit Value)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms







GHS02

GHS06

- · **Signal word** Danger
- · Hazard-determining components of labeling:

Methyl Alcohol

· Hazard statements

Highly flammable liquid and vapor.

Toxic if swallowed or in contact with skin.

Harmful if inhaled.

Causes damage to the central nervous system and the visual organs.

May cause damage to organs through prolonged or repeated exposure.

· Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

 $Do \ not \ breathe \ dust/fume/gas/mist/vapors/spray.$

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Immediately call a poison center/doctor.

Specific treatment (see on this label).

Rinse mouth.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF exposed: Call a POISON CENTER or doctor/physician.

Call a poison center/doctor if you feel unwell.

Get medical advice/attention if you feel unwell.

Take off immediately all contaminated clothing and wash it before reuse.

In case of fire: Use CO2, powder or water spray to extinguish.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 11)

Printing date 05/03/2022 Reviewed on 05/03/2022

Trade name: DIFFERENTIAL QUIK III FIXATIVE

(Contd. of page 10)

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Contact:
- · Date of preparation / last revision 05/03/2022 / -
- · Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

IC50. Lethal consentration 50 nearest

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flammable Liquids 2: Flammable liquids – Category 2

Acute Toxicity - Oral 3: Acute toxicity - Category 3

Acute Toxicity - Inhalation 4: Acute toxicity - Category 4

Specific Target Organ Toxicity - Single Exposure 1: Specific target organ toxicity (single exposure) - Category 1

Specific Target Organ Toxicity - Repeated Exposure 2: Specific target organ toxicity (repeated exposure) - Category 2

US