Printing date 10/20/2022 Reviewed on 10/20/2022

1 Identification

· Product identifier

· Trade name: DUST-OFF PRO

· Article number: 70845-00, 70845-01, 70845-12

• *CAS Number:* 75-37-6

• **EC number:** 200-866-1

· Application of the substance / the mixture Laboratory chemicals

Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

Electron Microscopy Sciences 1560 Industry Road USA-Hatfield, PA 19440

Tel: 215-412-8400 Fax: 215-412-8450

email: info@emsdiasum.com www.emsdiasum.com

· Information department: Product safety department

Emergency telephone number:

ChemTrec 1-800-424-9300 Contract CCN7661

1-703-527-3887

2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flammable Liquids 1

H224 Extremely flammable liquid and vapor.



GHS04 Gas cylinder

Gases under Pressure - Liquefied gas

GHS07

H280 Contains gas under pressure; may explode if heated.



Specific Target Organ Toxicity - Single Exposure 3 H336 May cause drowsiness or dizziness.

- · Label elements
- · GHS label elements The substance is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms







GHS02

GHS04

GHS07

- · Signal word Danger
- · Hazard statements

Contains gas under pressure; may explode if heated.

Extremely flammable liquid and vapor.

(Contd. on page 2)

Printing date 10/20/2022 Reviewed on 10/20/2022

Trade name: DUST-OFF PRO

(Contd. of page 1)

May cause drowsiness or dizziness.

· Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust/fume/gas/mist/vapors/spray

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Call a poison center/doctor if you feel unwell.

In case of fire: Use CO2, powder or water spray to extinguish.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Protect from sunlight. Store in a well-ventilated place.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 1Fire = 4Reactivity = 1

· HMIS-ratings (scale 0 - 4)



1 Health = 1Fire = 4

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Substances
- · CAS No. Description

75-37-6 1,1-difluoroethane

- · Identification number(s)
- · EC number: 200-866-1

4 First-aid measures

- · Description of first aid measures
- · General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist. (Contd. on page 3)

Printing date 10/20/2022 Reviewed on 10/20/2022

Trade name: DUST-OFF PRO

(Contd. of page 2)

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

Troccure fiction criteria for chemicus	
· PAC-1:	
	10,000 ppm
· PAC-2:	
	15,000 ppm
· PAC-3:	
	25,000 ppm

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect from heat.

Protect against electrostatic charges.

(Contd. on page 4)

Printing date 10/20/2022 Reviewed on 10/20/2022

Trade name: DUST-OFF PRO

(Contd. of page 3)

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep receptacle tightly sealed.

Do not gas tight seal receptacle.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

· Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace: Not required.
- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Compressed gas

Color: Clear

(Contd. on page 5)

Printing date 10/20/2022 Reviewed on 10/20/2022

Trade name: DUST-OFF PRO

	(Contd. of page
Odor:	Ether-like
Odor threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/Melting range:	-117 °C (-178.6 °F)
Boiling point/Boiling range:	-26.5 °C (-15.7 °F)
Flash point:	<23 °C (<73.4 °F)
Flammability (solid, gaseous):	Not determined.
Decomposition temperature:	Not determined.
Auto igniting:	Not determined.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vap mixtures are possible.
Explosion limits:	
Lower:	4.9 Vol %
Upper:	20.2 Vol %
Vapor pressure at 20 °C (68 °F):	5,100 hPa (3.800 mm Hg)
Density at 20 °C (68 °F):	0.91 g/cm³ (7.59395 lbs/gal)
Relative density	Not determined.
Vapor density	Not determined.
Evaporation rate	Not applicable.
Solubility in / Miscibility with	
Water at 20 °C (68 °F):	5 g/l
Partition coefficient (n-octanol/wate	er): Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
VOC content:	0.00 %
Solids content:	0.0 %
Other information	No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · *Incompatible materials:* No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

Printing date 10/20/2022 Reviewed on 10/20/2022

Trade name: DUST-OFF PRO

(Contd. of page 5)

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · LD/LC50 values that are relevant for classification:

75-37-6 1,1-difluoroethane

Inhalative LC50/4 h 977 mg/l (mouse)

- Primary irritant effect:
- · on the skin: No irritant effect.
- on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:
- · Carcinogenic categories
- · IARC (International Agency for Research on Cancer)

Substance is not listed.

· NTP (National Toxicology Program)

Substance is not listed.

· OSHA-Ca (Occupational Safety Health Administration)

Substance is not listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (Assessment by list): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- **Recommendation:** Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

US

Printing date 10/20/2022 Reviewed on 10/20/2022

Trade name: DUST-OFF PRO

(Contd. of page 6)

Transport information	
UN-Number DOT, ADR, IMDG, IATA	UN1030
	0.1110.50
UN proper shipping name DOT	1,1-Difluoroethane
ADR	1030 1,1-DIFLUOROETHANE (REFRIGERANT GAS R 152a)
IMDG, IATA	1,1-DIFLUOROETHANE (REFRIGERANT GAS R 152a)
Transport hazard class(es)	
DOT	
NAME OF	
Class	2.1 Gases
Label	2.1
ADR	
Class	2 2F Gases
Label	2.1
IMDG, IATA	
Class	2.1 Gases
Label	2.1
Packing group DOT, ADR, IMDG, IATA	Void
Environmental hazards:	Not applicable.
Special precautions for user	Warning: Gases
Hazard identification number (Kemler code):	
EMS Number:	F-D,S-U
Stowage Category	B CHA CL CL
Stowage Code	SW2 Clear of living quarters.
Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
DOT	
Quantity limitations	On passenger aircraft/rail: Forbidden
•	On cargo aircraft only: 150 kg

Printing date 10/20/2022 Reviewed on 10/20/2022

Trade name: DUST-OFF PRO

	(Contd. of page 7
· ADR	Code: E0
· Excepted quantities (EQ)	Not permitted as Excepted Quantity
· IMDG	0
· Limited quantities (LQ)	Code: E0
· Excepted quantities (EQ)	Not permitted as Excepted Quantity
· UN "Model Regulation":	UN 1030 1,1-DIFLUOROETHANE (REFRIGERANT GAS 1 152A), 2.1

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.
- · Sara
- · Section 355 (extremely hazardous substances):

Substance is not listed.

Section 313 (Specific toxic chemical listings):

Substance is not listed.

· TSCA (Toxic Substances Control Act):

ACTIVE

- · Hazardous Air Pollutants
- Substance is not listed.
- · Proposition 65
- · Chemicals known to cause cancer:

Substance is not listed.

· Chemicals known to cause reproductive toxicity for females:

Substance is not listed.

· Chemicals known to cause reproductive toxicity for males:

Substance is not listed.

· Chemicals known to cause developmental toxicity:

Substance is not listed.

- · Carcinogenic categories
- · EPA (Environmental Protection Agency)

Substance is not listed.

· TLV (Threshold Limit Value)

Substance is not listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

Substance is not listed.

· GHS label elements The substance is classified and labeled according to the Globally Harmonized System (GHS). (Contd. on page 9)

(Contd. of page 8)

Safety Data Sheet acc. to OSHA HCS

Printing date 10/20/2022 Reviewed on 10/20/2022

Trade name: DUST-OFF PRO

· Hazard pictograms







GHS02

2 GHS04

- · Signal word Danger
- · Hazard statements

Contains gas under pressure; may explode if heated.

Extremely flammable liquid and vapor.

May cause drowsiness or dizziness.

· Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust/fume/gas/mist/vapors/spray

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Call a poison center/doctor if you feel unwell.

In case of fire: Use CO2, powder or water spray to extinguish.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Protect from sunlight. Store in a well-ventilated place.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Contact:
- Date of preparation / last revision 10/20/2022 / -
- · Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit

(Contd. on page 10)

Printing date 10/20/2022 Reviewed on 10/20/2022

Trade name: DUST-OFF PRO

(Contd. of page 9)

 $REL: Recommended\ Exposure\ Limit$

Gases under Pressure - Liquefied gas: Gases under pressure - Liquefied gas
Flammable Liquids 1: Flammable liquids - Category 1
Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) - Category 3